

Customer	Date 12/22/2020
Contact	Project
Phone number	Project no.
Email	

1SV06T003T

1016L0050

Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m³ 1000
Static head	m 0	Kin. viscosity at t A	mm²/s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	l/s ()
Speed	rpm 2900	Flow Max-	l/s .7
Number of stages	6	Min-	l/s
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 341.3	Head at Qmax	m 14
Head H(Q=0)	m 35	at Qmin	m 34.8
Weight	kg 15	Shaft power	kW ()
Max.	m 115	Max. shaft power	kW .3
Impeller R designed	m 115	Efficiency	%
Min.	m 115	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304
Impeller	Stainless steel / AISI 304
Diffuser	Stainless steel / AISI 304
Outer sleeve	Stainless steel / AISI 304
Shaft	Stainless steel / AISI 304
Adapter	Cast iron
Base	Aluminium
Coupling	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 304
Tie rods	Galvanized steel
Wear Ring	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	400 V	Speed	2800 rpm	Insulation class	155 (F)
Specific design	Three phase surface motor (e-SV)			Frame size	71R	Colour	RAL 5010
Type	SM71RB14/304 (220-240/380-415V)						
Rated power	0.37 kW	Degree of protection	IP55				
Electric current	1.26 A						

Remarks:


Customer	Date	12/22/2020
Contact	Project	
Phone number	Project no.	
Email		

1SV06T003T 1016L0050

Hydraulic data

Operating Data Specification		Hydraulic data (duty point)	Impeller design	
Flow	0 l/s	Flow	Impeller R	114.96 m
Head	0 m	Head	Frequency	50 Hz
Static head	0 m	MEI $\geq 0,7$	Speed	2900 rpm

Power data referred to:
Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s
Performance according to ISO 9906:2012 – Grade 3B




Customer
Contact
Phone number
Email

Date 12/22/2020
Project
Project no.

1SV06T003T 1016L0050

Drawing



Dimensions m

D1	188.98					Weight
D2	165.35					14.6 kg
L1	532.28					
L2	329.13					
L5	492.91					
L6	492.91					
M	174.8					