

Customer	Date	12/22/2020
Contact	Project	
Phone number	Project no.	
Email		

1SV08N005M

1016L1894

Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	l/s ()
Speed	rpm 2900	Flow Max-	l/s .7
Number of stages	8	Min-	l/s
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 471.5	Head at Qmax	m 22.4
Head H(Q=0)	m 48	at Qmin	m 48.1
Weight	kg 15	Shaft power	kW ()
Max.	m 115	Max. shaft power	kW .4
Impeller R designed	m 115	Efficiency	%
Min.	m 115	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 316L
Impeller	Stainless steel / AISI 316L
Diffuser	Stainless steel / AISI 316L
Outer sleeve	Stainless steel / AISI 316L
Shaft	Stainless steel / AISI 316
Adapter	Cast iron
Base	Aluminium
Coupling	Aluminium
SEAL HOUSING	Stainless steel / AISI 316L
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 316
Tie rods	Stainless steel / AISI 431
Wear Ring	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	230 V	Speed	2820 rpm	Insulation class	155 (F)
Specific design	Single phase surface motor (e-SV)			Frame size	71	Colour	RAL 5010
Type	SM71B14/105 (220-240V)						
Rated power	0.55 kW	Degree of protection IP55					
Electric current	3.99 A						

Remarks:

Customer	Date	12/22/2020
Contact	Project	
Phone number	Project no.	
Email		


1SV08N005M

1016L1894

Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 l/s	Flow		Impeller R	114.96 m
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,7		Speed	2900 rpm

Power data referred to:
 Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s
 Performance according to ISO 9906:2012 – Grade 3B



Customer	Date	12/22/2020
Contact	Project	
Phone number	Project no.	
Email		

1SV08N005M
1016L1894

Drawing



Dimensions m

D1	220.47					Weight 15.2 kg
D2	165.35					
L1	595.28					
L2	363.78					
L3	595.28					
L4	357.48					
L5	555.91					
L6	555.91					
M	190.55					