

Customer	Date	12/10/2020
Contact	Project	
Phone number	Project no.	
Email		

10SV02F007T
1016LD161
Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	l/s ()
Speed	rpm 2900	Flow	Max- l/s 3.9
Number of stages	2		Min- l/s
Max. casing pressure	kPa		Nominal m
Max. working pressure	kPa 231.8	Head	at Qmax m 10
Head H(Q=0)	m 24		at Qmin m 23.6
Weight	kg 25	Shaft power	kW ()
	Max. mm 96	Max. shaft power	kW .7
Impeller R	designed mm 96	Efficiency	%
	Min. mm 96	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304
Impeller	Stainless steel / AISI 304
Diffuser	Stainless steel / AISI 304
Outer sleeve	Stainless steel / AISI 304
Shaft	Stainless steel / AISI 304
Adapter	Cast iron
Base	Aluminium
Coupling	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 304
Tie rods	Galvanized steel
Wear Ring	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	220 V	Speed	2895 rpm	Insulation class	155 (F)
Specific design	IE3 Three phase surface motor (e-SV)			Frame size	80	Colour	RAL 5010
Type	SM80B14/307 PE (220-240/380-415V)						
Rated power	0.75 kW	Degree of protection IP55					
Electric current	2.96 A						

Remarks:

Customer	Date	12/10/2020
Contact	Project	
Phone number	Project no.	
Email		

10SV02F007T

1016LD161


Hydraulic data

Operating Data Specification		Hydraulic data (duty point)	Impeller design	
Flow	0 l/s	Flow	Impeller R	96 mm
Head	0 m	Head	Frequency	50 Hz
Static head	0 m	MEI >=0,7	Speed	2900 rpm

Power datas referred to:

Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s

Performance according to ISO 9906:2012 – Grade 3B




Customer	Date	12/10/2020
Contact	Project	
Phone number	Project no.	
Email		

10SV02F007T

1016LD161

Drawing



Dimensions mm

D1	155					Weight	
D2	120					24.9	kg
L1	357						
L2	263						
L5	357						
L6	367						
M	129						

05908_B_DD