

Customer	Date	12/10/2020
Contact	Project	
Phone number	Project no.	
Email		

10SV09F040T

1016LD231

Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m³ 1000
Static head	m 0	Kin. viscosity at t A	mm²/s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	l/s ()
Speed	rpm 2900	Flow	Max- l/s 3.9
Number of stages	9	Min-	l/s
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 1042.8	Head	at Qmax m 51.9
Head H(Q=0)	m 110	at Qmin	m 106.3
Weight	kg 50	Shaft power	kW ()
Max.	mm 96	Max. shaft power	kW 3.3
Impeller R	designed mm 96	Efficiency	%
Min.	mm 96	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304	e-SV Mechanical seal	Roten
Impeller	Stainless steel / AISI 304	e-SV - Uniten (-30 / +120 °C)	
Diffuser	Stainless steel / AISI 304	1 - Rotating part	Silicon Carbide
Outer sleeve	Stainless steel / AISI 304	2 - Stationary part	Resin impregnated carbon
Shaft	Stainless steel / AISI 304	3 - Elastomers	EPDM
Adapter	Cast iron	4 - Springs	AISI 316
Base	Aluminium	5 - Other components	AISI 316
Coupling	Aluminium		
SEAL HOUSING	Stainless steel / AISI 304		
Coupling protection	Stainless steel / AISI 304		
Shaft sleeve and bushing	Tungsten carbide		
Fill / drain plugs	Stainless steel / AISI 304		
Tie rods	Galvanized steel		
Wear Ring	Technopolymer PPS		

Motor data

Manufacturer	Lowara	Electric voltage	400 V	Speed	2910 rpm	Insulation class	155 (F)
Specific design	IE3 Three phase surface motor (e-SV)	Frame size	112R	Colour			RAL 5010
Type	PLM112RB14S6/340 E3 (220-240/380-415V)						
Rated power	4 kW	Degree of protection	IP55				
Electric current	7.75 A						

Remarks:

Customer	Date	12/10/2020
Contact	Project	
Phone number	Project no.	
Email		

10SV09F040T

1016LD231


Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 l/s	Flow		Impeller R	96 mm
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,7		Speed	2900 rpm

Power datas referred to:

Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s

Performance according to ISO 9906:2012 – Grade 3B




Customer	Date	12/10/2020
Contact	Project	
Phone number	Project no.	
Email		

10SV09F040T

1016LD231

Drawing



Dimensions mm

D1	197					Weight
D2	160					49.7
L1	601					kg
L2	319					
L3	601					
L4	387					
L5	601					
L6	611					
M	154					