

Customer Contact	Date	1/7/2021
Phone number	Project	
Email	Project no.	

22SV07T075T

1016LD670

Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	l/s ()
Speed	rpm 2900	Flow	Max- l/s 8.1
Number of stages	7	Min-	l/s
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 1064.4	Head	at Qmax m 48.8
Head H(Q=0)	m 110	at Qmin	m 108.5
Weight	kg 86	Shaft power	kW ()
Max.	m 170.1	Max. shaft power	kW 7.2
Impeller R	designed m 170.1	Efficiency	%
Min.	m 170.1	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304
Impeller	Stainless steel / AISI 304
Diffuser	Stainless steel / AISI 304
Outer sleeve	Stainless steel / AISI 304
Shaft	Stainless steel / AISI 304
Adapter	Cast iron
Base	Aluminium
Coupling	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 304
Tie rods	Galvanized steel
Wear Ring	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	400 V	Speed	2935 rpm	Insulation class	155 (F)
Specific design	IE3 Three phase surface motor (e-SV)	Frame size	132	Colour			RAL 5010
Type	PLM132B5/375 E3 (220-240/380-415V)						
Rated power	7.5 kW	Degree of protection	IP55				
Electric current	14.1 A						

Remarks:


Customer	Date	1/7/2021
Contact	Project	
Phone number	Project no.	
Email		

22SV07T075T 1016LD670

Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 l/s	Flow		Impeller R	170.08 m
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,7		Speed	2900 rpm


Power data referred to:
 Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s
 Performance according to ISO 9906:2012 – Grade 3B



Customer	Date	1/7/2021
Contact	Project	
Phone number	Project no.	
Email		

22SV07T075T
1016LD670

Drawing



Dimensions m

D1	403.15					Weight 86 kg
D2	472.44					
L1	1143.3					
L2	577.95					
L3	1143.3					
L4	700.79					
L5	1143.3					
M	300.79					

05910_B_DD