

Customer	Date	12/8/2020
Contact	Project	
Phone number	Project no.	
Email		

## ESHE 80-250/55/P45VSNA

101863740

### Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m <sup>3</sup> 1000
Static head	m 0	Kin. viscosity at t A	mm <sup>2</sup> /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

### Pump data

Make	Lowara	Nominal	l/s ( )
Speed	rpm 1450	Flow Max-	l/s 35
Number of stages	1	Min-	l/s 12.5
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 199.2	Head at Qmax	m 9
Head H(Q=0)	m 20	at Qmin	m 19.5
Weight	kg	Shaft power	kW ( )
Max. Impeller R	mm 270	Max. shaft power	kW 5.2
designed	mm 237	Efficiency	%
Min.	mm 237	NPSH 3%	m
Suction nozzle	DN 100 PN 12 EN1092-2 (e-SH)	Discharge nozzle	DN 80 PN 12 EN1092-2 (e-SH)

### Pump Materials

Pump body	Stainless steel / AISI 316L
Impeller	Stainless steel / ASTM CF8M
SEAL HOUSING	Stainless steel / AISI 316L
Wear Ring	Stainless steel / AISI 316L
Counterwear ring	Stainless steel / AISI 316L
Shaft extension	Stainless steel / AISI 316L
Rigid shaft coupling	Stainless steel / AISI 316
Impeller locknut and washer	Stainless steel / AISI 316
Tab	Stainless steel / AISI 316L

### Shaft Seal

Single Seal	
e-SH - uniten	Roten
Rotating Assembly	V-Ceramic
Fixed Assembly	B-Resin impregnated carbon
Elastomers	V-FKM (FPM)
Springs	G-AISI 316
Other Components	G-AISI 316

### Motor data

Manufacturer	Lowara	Electric voltage	400 V
Specific design	IE3 Three phase surface motor		
Type	PLM4132.../355 E3		
Rated power	5.5 kW	Electric current	11.5 A
Speed	1465 rpm	Degree of protection	IP 55
Frame size	132	Weight	58 kg
Shaft diameter	0 mm	Colour	RAL 5010
Insulation class	F		

### Coupling

Manufacturer	
Series	
Type	
Frame size	
Spacer length	
Weight	
Coupling protection	

### Base plate

Description	
Weight	

### Remarks:

Customer	Date	12/8/2020
Contact	Project	
Phone number	Project no.	
Email		

## ESHE 80-250/55/P45VSNA

### 101863740

#### Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 l/s	Flow		Impeller R	237 mm
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,4		Speed	1450 rpm

Power data referred to:  
 Water, pure [100%] ; 4°C; 1000kg/m<sup>3</sup>; 1.57mm<sup>2</sup>/s  
 Performance according to ISO 9906:2012 – Grade 3B



