

Qty. Description

1 SP 125-14



Note! Product picture may differ from actual product

Product No.: [17AK4314](#)

Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4301 (AISI 304), that ensures high corrosive resistance. This pump carries drinking water approval.

The pump is fitted with a 147 kW MMS10000 motor with sand shield, water-lubricated journal bearings and a volume compensating diaphragm. The rewindable motor construction allows complete access to the windings for easy rewinding. The stator windings are PE/PA insulated made for continuous operations (S1). Suitable for temperatures up to 50 °C. The motor is fitted with a mechanical shaft seal.

The motor is not fitted with a temperature sensor. If temperature monitoring is desired, a Pt100 or Pt1000 sensor can be fitted.

The motor is for direct-on-line starting (DOL).


Further product details

The pump is suitable for applications similar to the following:

- raw-water supply
- irrigation
- groundwater lowering
- pressure boosting
- fountain applications.

Pump

All pump surfaces that are in contact with pumped liquids are made in stainless steel which makes them corrosion- and wear-resistant. The corrosion diagram below shows the capabilities of the pump and motor in relation to the temperature in Celsius (y-axis) and the concentration of chloride in ppm (x-axis).



The elastomer parts in the pump are made of NBR (Nitrile-Butadiene Rubber) which ensures good wear resistance and long service intervals.

In case the pump is used for pumping water with high content of hydrocarbons or solvents, Grundfos offers FKM rubber parts (Fluorocarbon) which are oil and temperature-resistant up to 90 °C.

Qty.	Description																																																								
	<p>The pump is built with octagonal bearings with sand flush channels that minimise wear. As wear of the pump is inevitable, the pump design allows for easy replacement of all internal wear parts (bearings, impeller, wear rings and seal rings) to maintain high performance and a long lifetime.</p> <p>The suction interconnector is fitted with a strainer to prevent large particles from entering the pump.</p> <p>Motor</p> <p>The winding wire is made from pure electrolytic copper insulated by extruded two layers of PE/PA with high dielectric strength properties allowing direct contact between the motor fluid and winding wire. This ensures the best possible cooling of the winding wire. The PA layer ensures high mechanical wear properties of the winding wire.</p> <p>The shaft seal faces are SiC/SiC. The material combination gives good performance when abrasive particles (sand) is present. Together with the shaft seal housing, the sand shield forms a labyrinth seal, which during normal operating conditions prevents penetration of sand particles into the shaft seal. This shaft seal is drinking water approved.</p> <p>The motor can be fitted with a Pt100 or Pt1000 sensor that together with a control unit ensures that the maximum operating temperature conditions are not exceeded.</p> <p>Liquid:</p> <table border="0"> <tr> <td>Pumped liquid:</td> <td>Water</td> </tr> <tr> <td>Maximum liquid temperature:</td> <td>45 °C</td> </tr> <tr> <td>Max liquid t at 0.15 m/sec:</td> <td>40 °C</td> </tr> <tr> <td>Max liquid t at 0.5 m/sec:</td> <td>45 °C</td> </tr> <tr> <td>Selected liquid temperature:</td> <td>20 °C</td> </tr> <tr> <td>Density:</td> <td>998.2 kg/m³</td> </tr> </table> <p>Technical:</p> <table border="0"> <tr> <td>Pump speed on which pump data are based:</td> <td>2900 rpm</td> </tr> <tr> <td>Rated flow:</td> <td>125 m³/h</td> </tr> <tr> <td>Rated head:</td> <td>287 m</td> </tr> <tr> <td>Shaft seal for motor:</td> <td>SIC/SIC</td> </tr> <tr> <td>Curve tolerance:</td> <td>ISO9906:2012 3B</td> </tr> <tr> <td>Motor version:</td> <td>T45</td> </tr> </table> <p>Materials:</p> <table border="0"> <tr> <td>Pump:</td> <td>Stainless steel EN 1.4301 AISI AISI 304</td> </tr> <tr> <td>Impeller:</td> <td>Stainless steel EN 1.4301 AISI AISI 304</td> </tr> <tr> <td>Motor:</td> <td>Cast iron DIN W.-Nr. 0.6025 ASTM 35-40</td> </tr> </table> <p>Installation:</p> <table border="0"> <tr> <td>Pump outlet:</td> <td>RP6</td> </tr> <tr> <td>Motor diameter:</td> <td>10 inch</td> </tr> </table> <p>Electrical data:</p> <table border="0"> <tr> <td>Motor type:</td> <td>MMS10000</td> </tr> <tr> <td>Rated power - P2:</td> <td>147 kW</td> </tr> <tr> <td>Power (P2) required by pump:</td> <td>147 kW</td> </tr> <tr> <td>Mains frequency:</td> <td>50 Hz</td> </tr> <tr> <td>Rated voltage:</td> <td>3 x 380-400-415 V</td> </tr> <tr> <td>Rated current:</td> <td>315-315-320 A</td> </tr> <tr> <td>Starting current:</td> <td>580-620-630 %</td> </tr> <tr> <td>Cos phi - power factor:</td> <td>0.85-0.81-0.77</td> </tr> <tr> <td>Rated speed:</td> <td>2920-2920-2930 rpm</td> </tr> <tr> <td>Start. method:</td> <td>direct-on-line</td> </tr> <tr> <td>Enclosure class (IEC 34-5):</td> <td>IP68</td> </tr> </table>	Pumped liquid:	Water	Maximum liquid temperature:	45 °C	Max liquid t at 0.15 m/sec:	40 °C	Max liquid t at 0.5 m/sec:	45 °C	Selected liquid temperature:	20 °C	Density:	998.2 kg/m ³	Pump speed on which pump data are based:	2900 rpm	Rated flow:	125 m ³ /h	Rated head:	287 m	Shaft seal for motor:	SIC/SIC	Curve tolerance:	ISO9906:2012 3B	Motor version:	T45	Pump:	Stainless steel EN 1.4301 AISI AISI 304	Impeller:	Stainless steel EN 1.4301 AISI AISI 304	Motor:	Cast iron DIN W.-Nr. 0.6025 ASTM 35-40	Pump outlet:	RP6	Motor diameter:	10 inch	Motor type:	MMS10000	Rated power - P2:	147 kW	Power (P2) required by pump:	147 kW	Mains frequency:	50 Hz	Rated voltage:	3 x 380-400-415 V	Rated current:	315-315-320 A	Starting current:	580-620-630 %	Cos phi - power factor:	0.85-0.81-0.77	Rated speed:	2920-2920-2930 rpm	Start. method:	direct-on-line	Enclosure class (IEC 34-5):	IP68
Pumped liquid:	Water																																																								
Maximum liquid temperature:	45 °C																																																								
Max liquid t at 0.15 m/sec:	40 °C																																																								
Max liquid t at 0.5 m/sec:	45 °C																																																								
Selected liquid temperature:	20 °C																																																								
Density:	998.2 kg/m ³																																																								
Pump speed on which pump data are based:	2900 rpm																																																								
Rated flow:	125 m ³ /h																																																								
Rated head:	287 m																																																								
Shaft seal for motor:	SIC/SIC																																																								
Curve tolerance:	ISO9906:2012 3B																																																								
Motor version:	T45																																																								
Pump:	Stainless steel EN 1.4301 AISI AISI 304																																																								
Impeller:	Stainless steel EN 1.4301 AISI AISI 304																																																								
Motor:	Cast iron DIN W.-Nr. 0.6025 ASTM 35-40																																																								
Pump outlet:	RP6																																																								
Motor diameter:	10 inch																																																								
Motor type:	MMS10000																																																								
Rated power - P2:	147 kW																																																								
Power (P2) required by pump:	147 kW																																																								
Mains frequency:	50 Hz																																																								
Rated voltage:	3 x 380-400-415 V																																																								
Rated current:	315-315-320 A																																																								
Starting current:	580-620-630 %																																																								
Cos phi - power factor:	0.85-0.81-0.77																																																								
Rated speed:	2920-2920-2930 rpm																																																								
Start. method:	direct-on-line																																																								
Enclosure class (IEC 34-5):	IP68																																																								



Company name:

Created by:


Phone:

Date:





10/11/2020

Qty.	Description
	<p>Built-in temp. transmitter: no Motor No: 96540302 Windings: PE2/PA</p> <p>Others: Minimum efficiency index, MEI $\eta_{\%}$: --- ErP status: EuP Standalone/Prod. Net weight: 645 kg Gross weight: 715 kg Shipping volume: 1.45 m³ Country of origin: DK Custom tariff no.: 84137029</p>

17AK4314 SP 125-14 50 Hz



Description	Value
General information:	
Product name:	SP 125-14
Product No:	17AK4314
EAN number:	5710626356546
Technical:	
Pump speed on which pump data are based:	2900 rpm
Rated flow:	125 m³/h
Rated head:	287 m
Stages:	14
Impeller reduc.:	NONE
Shaft seal for motor:	SIC/SIC
Curve tolerance:	ISO9906:2012 3B
Model:	D
Valve:	YES
Motor version:	T45
Materials:	
Pump:	Stainless steel
Pump:	EN 1.4301
Pump:	AISI AISI 304
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI AISI 304
Motor:	Cast iron
Motor:	DIN W.-Nr. 0.6025
Motor:	ASTM 35-40
Installation:	
Pump outlet:	RP6
Motor diameter:	10 inch
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	45 °C
Max liquid t at 0.15 m/sec:	40 °C
Max liquid t at 0.5 m/sec:	45 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	MMS10000
Applic. motor:	GRUNDFOS
Rated power - P2:	147 kW
Power (P2) required by pump:	147 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Rated current:	315-315-320 A
Starting current:	580-620-630 %
Cos phi - power factor:	0.85-0.81-0.77
Rated speed:	2920-2920-2930 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	no
Motor No:	96540302
Windings:	PE2/PA
Others:	
Minimum efficiency index, MEI $\hat{a}\%$ ¥:	---
ErP status:	EuP Standalone/Prod.
Net weight:	645 kg





Company name:

Created by:


Phone:

Date:


10/11/2020

Description	Value
Gross weight:	715 kg
Shipping volume:	1.45 m ³
Country of origin:	DK
Custom tariff no.:	84137029

17AK4314 SP 125-14 50 Hz




17AK4314 SP 125-14 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

17AK4314 SP 125-14 50 Hz



Note! All units are in [mm] unless others are stated.