

Data sheet: Stratos GIGA 100/1-17/3,7

Hydraulic data

Minimum efficiency index (MEI)	0.7
Maximum operating pressure p	16 bar
Min. fluid temperature T_{min}	-20 °C
Max. fluid temperature T_{max}	140 °C
Min. ambient temperature T_{min}	0 °C
Max. ambient temperature T_{max}	40 °C

Materials

Pump housing	EN-GJL-250
Impeller	PPS-GF40
Shaft	1.4542
Shaft seal	AQ1EGG
Lantern	5.1301, KTL-coated

Installation dimensions

Pipe connection on the suction side <i>DN_s</i>	DN 100
Pipe connection on the pressure side <i>DN_d</i>	DN 100

Motor data

Mains connection	3~400 V, 50/60 Hz
Motor efficiency class	IE5
Rated power P_2	3.70 kW
Rated current I_N	7.30 A
Rated speed n	2300 rpm
Max. speed n_{max}	2300 rpm
Power consumption $P_{1 max}$	4100.0 W
Emitted interference	EN 61800-3
Interference resistance	EN 61800-3
Insulation class	F
Protection class motor	IP55
Threaded cable connection	1 x M12x1.5

Approved liquids (other liquids upon request)

Heating water (as per VDI 2035)	yes
Heat carrier oil	Special version at additional charge
Cooling and cold water circulation systems	yes
Water-glycol mixtures (at 20 – 40 vol. % glycol and fluid temperature \leq 40 °C)	yes

Information for order placements

Brand	Wilo
Product description	Stratos GIGA 100/1-17/3,7
EAN number	4048482794068
Article number	2170134
Net weight, approx. m	67 kg
Gross weight, approx. m	73.7 kg
Length with packaging	795 mm
Height with packaging	615 mm
Width with packaging	515 mm
Packaging property	Transport packaging
Packaging type	Package
Minimum order quantity	1

Dimensions and dimensions drawings: Stratos GIGA 100/1-17/3,7

Stratos GIGA 100/1-17/3,7

