

Data sheet: Stratos GIGA-D 50/1-33/2,6

Hydraulic data

Minimum efficiency index (MEI)	0.7
Maximum operating pressure p	16 bar
Min. fluid temperature T_{min}	-20 °C
Max. fluid temperature T_{max}	140 °C
Min. ambient temperature T_{min}	0 °C
Max. ambient temperature T_{max}	40 °C

Materials

Pump housing	EN-GJL-250
Impeller	PPS-GF40
Shaft	1.4542
Shaft seal	AQ1EGG
Lantern	5.1301, KTL-coated

Installation dimensions

Pipe connection on the suction side <i>DN_s</i>	DN 50
Pipe connection on the pressure side <i>DN_d</i>	DN 50

Motor data

Mains connection	3~400 V, 50/60 Hz
Motor efficiency class	IE5
Rated power P_2	2.60 kW
Rated current I_N	5.50 A
Rated speed n	4620 rpm
Max. speed n_{max}	4620 rpm
Power consumption $P_{1 max}$	3000.0 W
Emitted interference	EN 61800-3
Interference resistance	EN 61800-3
Insulation class	F
Protection class motor	IP55
Threaded cable connection	1 x M12x1.5

Approved liquids (other liquids upon request)

Heating water (as per VDI 2035)	yes
Heat carrier oil	Special version at additional charge
Cooling and cold water circulation systems	yes
Water-glycol mixtures (at 20 – 40 vol. % glycol and fluid temperature \leq 40 °C)	yes

Information for order placements

Brand	Wilo
Product description	Stratos GIGA-D 50/1-33/2,6
EAN number	4048482708553
Article number	2170227
Net weight, approx. m	84 kg
Gross weight, approx. m	95.0 kg
Length with packaging	790 mm
Height with packaging	665.6 mm
Width with packaging	590 mm
Packaging property	Transport packaging
Packaging type	One-way pallet
Minimum order quantity	1