



Performance according to ISO 9906:2012 – Grade 3B

Power data referred to:

Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s

Operating Data Specification

| | |
|-------------|-------|
| Flow | 0 l/s |
| Head | 0 m |
| Power input | |

Pump data

| | |
|------------------------------|--------|
| Pressure rating | PN 6 |
| Weight | 2.4 kg |
| * No condensing, no freezing | |

Materials

| | |
|----------------------|---|
| Pump body | Cast iron cataphoretically coated |
| Rotor assembly group | Stainless steel / Composite material / Carbon |
| Bearing | Ceramics |
| Gaskets | EPDM Rubber |
| Motor housing | Aluminium |
| Screw ring | Aluminium |
| Plug | Poly amide |

Motor data

| | | | |
|-------------------------|----------|------------|--------|
| Energy efficiency class | A | | |
| Max Power | 0.042 kW | max Strom | 0.47 A |
| Rated voltage | 230 V | Frequency | 50 |
| Insulation class | F | Protection | IP 44 |

Dimensions mm

| | |
|----|----------------------------------|
| D | Rp 1" |
| DN | 25 |
| F | G 1" ¹ / ₂ |
| H | 180 |
| H1 | 90 |

