

Qty.	Description
------	-------------

1	Unilift AP50.50.11.3.V
---	-------------------------------



Note! Product picture may differ from actual product

Product No.: [96010562](#)

Submersible drainage pump type

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.

The impeller is a VORTEX impeller for 50 mm free passage suitable for pumping groundwater, surface water, rain water and similar.

The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.

The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.

The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.

Liquid:

Liquid temperature range: 0 .. 55 °C



Density at selected liquid temperature: 998.2 kg/m³

Technical:

Type of impeller: VORTEX

Qty.	Description
	<p>Maximum particle size: 50 mm</p> <p>Materials:</p> <p>Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation:</p> <p>Pump outlet: Rp 2 Maximum installation depth: 7 m</p> <p>Electrical data:</p> <p>Power input - P1: 1.9 kW Mains frequency: 50 Hz Rated voltage: 3 x 400 V Rated current: 3 A Cos phi - power factor: 0.88 Rated speed: 2785 rpm Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others:</p> <p>Net weight: 15 kg Gross weight: 16 kg Danish VVS No.: 391322132 Swedish RSK No.: 5880120 Country of origin: HU Custom tariff no.: 84137021</p>

96010562 Unilift AP50.50.11.3.V 50 Hz



Description	Value
-------------	-------

General information:

Product name:	Unilift AP50.50.11.3.V
Product No:	96010562
EAN number:	5700390900564
	5700390900564
Price:	1.878,00 GBP

Technical:

Max flow:	8.89 l/s
Head max:	13 m
Type of impeller:	VORTEX
Maximum particle size:	50 mm

Materials:

Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304

Installation:

Pump outlet:	Rp 2
Maximum installation depth:	7 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical

Liquid:

Liquid temperature range:	0 .. 55 °C
Density at selected liquid temperature:	998.2 kg/m ³

Electrical data:

Power input - P1:	1.9 kW
P2:	1.2 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 400 V
Rated current:	3 A
Cos phi - power factor:	0.88
Rated speed:	2785 rpm
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Length of cable:	10 m
Type of cable plug:	NONE

Others:

Net weight:	15 kg
Gross weight:	16 kg
Danish VVS No.:	391322132
Swedish RSK No.:	5880120
Country of origin:	HU
Custom tariff no.:	84137021

