

Qty.	Description
------	-------------

1	Unilift AP12.40.08.A3
---	------------------------------



Note! Product picture may differ from actual product

Product No.: [96010925](#)

Submersible drainage pump type

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.

The pump is supplied with a control box including motor starter and motor protection and with an 0.8 m mains cable. Furthermore, the pump is supplied with level switch for automatic start and stop and 10 m level switch cable.

The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.

The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.

The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.

The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.

Liquid:

Liquid temperature range: 0 .. 55 °C

Density at selected liquid temperature: 998.2 kg/m³


Technical:

Type of impeller: SEMI OPEN

Maximum particle size: 12 mm

Qty.	Description
	<p>Materials:</p> <p>Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation:</p> <p>Pump outlet: Rp 1 1/2 Maximum installation depth: 7 m</p> <p>Electrical data:</p> <p>Power input - P1: 1.2 kW Mains frequency: 50 Hz Rated voltage: 3 x 400 V Rated current: 2.1 A Cos phi - power factor: 0.87 Rated speed: 2810 rpm Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others:</p> <p>Net weight: 14 kg Gross weight: 15 kg Danish VVS No.: 391314331 Swedish RSK No.: 5880112 Country of origin: HU Custom tariff no.: 84137021</p>

96010925 Unilift AP12.40.08.A3 50 Hz



Description	Value
General information:	
Product name:	Unilift AP12.40.08.A3
Product No:	96010925
EAN number:	5700390901011
	5700390901011
Price:	1.038,00 GBP
Technical:	
Max flow:	5.83 l/s
Head max:	15 m
Type of impeller:	SEMI OPEN
Maximum particle size:	12 mm
Materials:	
Pump housing:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Impeller:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Installation:	
Pump outlet:	Rp 1 1/2
Maximum installation depth:	7 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical
Liquid:	
Liquid temperature range:	0 .. 55 °C
Density at selected liquid temperature:	998.2 kg/m ³
Electrical data:	
Power input - P1:	1.2 kW
P2:	0.8 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 400 V
Rated current:	2.1 A
Cos phi - power factor:	0.87
Rated speed:	2810 rpm
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Length of cable:	10 m
Type of cable plug:	NONE
Controls:	
Level switch:	float switch
Others:	
Net weight:	14 kg
Gross weight:	15 kg
Danish VVS No.:	391314331
Swedish RSK No.:	5880112
Country of origin:	HU
Custom tariff no.:	84137021

