

**Qty. Description**

1 **Unilift AP12.50.11.A3**



Note! Product picture may differ from actual product

Product No.: [96010927](#)

Submersible drainage pump type

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.

The pump is supplied with a control box including motor starter and motor protection and with an 0.8 m mains cable. Furthermore, the pump is supplied with level switch for automatic start and stop and 10 m level switch cable.

The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.

The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.

The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.

The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.

**Liquid:**

Liquid temperature range: 0 .. 55 °C

Density at selected liquid temperature: 998.2 kg/m<sup>3</sup>


**Technical:**

Type of impeller: SEMI OPEN

Maximum particle size: 12 mm



## 96010927 Unilift AP12.50.11.A3 50 Hz



Description	Value
<b>General information:</b>	
Product name:	Unilift AP12.50.11.A3
Product No:	96010927
EAN number:	5700390901059
	5700390901059
Price:	1.396,00 GBP
<b>Technical:</b>	
Max flow:	8.89 l/s
Head max:	18 m
Type of impeller:	SEMI OPEN
Maximum particle size:	12 mm
<b>Materials:</b>	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
<b>Installation:</b>	
Pump outlet:	Rp 2
Maximum installation depth:	7 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical
<b>Liquid:</b>	
Liquid temperature range:	0 .. 55 °C
Density at selected liquid temperature:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Power input - P1:	1.9 kW
P2:	1.2 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 400 V
Rated current:	3.2 A
Cos phi - power factor:	0.88
Rated speed:	2785 rpm
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Length of cable:	10 m
Type of cable plug:	NONE
<b>Controls:</b>	
Level switch:	float switch
<b>Others:</b>	
Net weight:	17.5 kg
Gross weight:	18 kg
Danish VVS No.:	391314312
Swedish RSK No.:	5880113
Country of origin:	HU
Custom tariff no.:	84137021

