


Qty.	Description
1	<p data-bbox="199 336 351 369">SP 270-3A G</p>  <p data-bbox="590 772 1077 795" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="199 801 470 828">Product No.: 96430970</p> <p data-bbox="199 833 1452 884">Multi-stage submersible pump for raw water supply, groundwater lowering, pressure boosting and various industrial jobs.</p> <p data-bbox="199 889 1284 918">The pump is suitable for pumping clean, thin, non-aggressive liquids without solid particles or fibres.</p> <p data-bbox="199 952 1428 996">Pump: The pump is made entirely of Cast iron DIN W.-Nr. EN-JL1040 and suitable for horizontal installation.</p> <p data-bbox="199 1008 742 1037">The pump is fitted with a built-in non-return valve.</p> <p data-bbox="199 1070 1412 1120">Phase: The motor is a 3-phase motor with sand shield, liquid-lubricated bearings and pressure equalizing diaphragm.</p> <p data-bbox="199 1126 1077 1155">Performance test according to ISO9906 2012 Grade 3B is available on request.</p> <p data-bbox="199 1187 702 1361">Liquid: Pumped liquid: Water Maximum liquid temperature: 40 °C Max liquid t at 0.15 m/sec: 25 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³</p> <p data-bbox="199 1393 821 1630">Technical: Pump speed on which pump data are based: 2900 rpm Rated flow: 270 m³/h Rated head: 86 m Type of impeller: A Shaft seal for motor: CER/CARBON Curve tolerance: ISO9906:2012 3B Motor version: T30</p> <p data-bbox="199 1662 805 1899">Materials: Pump: Cast iron EN-JL1040 Impeller: Zinc-free bronze DIN W.-Nr. 2.1050.01 Motor: Cast iron DIN W.-Nr. 0.6025 ASTM 35-40</p> <p data-bbox="199 1930 646 2049">Installation: Flange standard: DIN Pump outlet: DN175 Motor diameter: 8 inch</p> <p data-bbox="199 2080 367 2110">Electrical data:</p>



Company name:

Created by:

Phone:

Date:


12/11/2020

Qty. Description





Motor type: MMS8000
Rated power - P2: 92 kW
Mains frequency: 50 Hz
Rated voltage: 3 x 380-400-415 V
Rated current: 194-186-186 A
Cos phi - power factor: 0.88-0.86-0.83
Rated speed: 2870-2890-2890 rpm
Start. method: direct-on-line
Enclosure class (IEC 34-5): IP68
Built-in temp. transmitter: no
Motor No: 96430675
Windings: PVC

Others:
Net weight: 473 kg
Shipping volume: 0.692 m³
Country of origin: IT
Custom tariff no.: 84137029



96430970 SP 270-3A G 50 Hz



Description	Value
General information:	
Product name:	SP 270-3A G
Product No:	96430970
EAN number:	5700392954299
Technical:	
Pump speed on which pump data are based:	2900 rpm
Rated flow:	270 m ³ /h
Rated head:	86 m
Stages:	3
Type of impeller:	A
Shaft seal for motor:	CER/CARBON
Curve tolerance:	ISO9906:2012 3B
Pump No:	96430861
Model:	A
Valve:	pump with built-in non-return valve
Motor version:	T30
Materials:	
Pump:	Cast iron
Pump:	EN-JL1040
Impeller:	Zinc-free bronze
Impeller:	DIN W.-Nr. 2.1050.01
Motor:	Cast iron
Motor:	DIN W.-Nr. 0.6025
Motor:	ASTM 35-40
Installation:	
Flange standard:	DIN
Pump outlet:	DN175
Motor diameter:	8 inch
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	40 °C
Max liquid t at 0.15 m/sec:	25 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Motor type:	MMS8000
Applic. motor:	GRUNDFOS
Rated power - P2:	92 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Rated current:	194-186-186 A
Cos phi - power factor:	0.88-0.86-0.83
Rated speed:	2870-2890-2890 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	no
Motor No:	96430675
Windings:	PVC
Others:	
Net weight:	473 kg
Shipping volume:	0.692 m ³
Country of origin:	IT
Custom tariff no.:	84137029




96430970 SP 270-3A G 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96430970 SP 270-3A G 50 Hz



Note! All units are in [mm] unless others are stated.