

Qty. Description

1 **SP 360-4F G**



Note! Product picture may differ from actual product

Product No.: [96431017](#)

Multi-stage submersible pump for raw water supply, groundwater lowering, pressure boosting and various industrial jobs.

The pump is suitable for pumping clean, thin, non-aggressive liquids without solid particles or fibres.

Pump: The pump is made entirely of Cast iron DIN W.-Nr. EN-JL1040 and suitable for horizontal installation.

The pump is fitted with a built-in non-return valve.

Phase: The motor is a 3-phase motor with sand shield, liquid-lubricated bearings and pressure equalizing diaphragm.

Performance test according to ISO9906 2012 Grade 3B is available on request.

Liquid:
 Pumped liquid: Water
 Maximum liquid temperature: 40 °C
 Max liquid t at 0.15 m/sec: 25 °C
 Selected liquid temperature: 20 °C
 Density: 998.2 kg/m³

Technical:
 Pump speed on which pump data are based: 2900 rpm
 Rated flow: 360 m³/h
 Rated head: 119 m
 Type of impeller: F
 Shaft seal for motor: CER/CARBON
 Curve tolerance: ISO9906:2012 3B
 Motor version: T30

Materials:
Pump: Cast iron
 EN-JL1040
Impeller: Zinc-free bronze
 DIN W.-Nr. 2.1050.01
Motor: Cast iron
 DIN W.-Nr. 0.6025
 ASTM 35-40

Installation:
 Flange standard: DIN
 Pump outlet: DN175
 Motor diameter: 12 inch

Electrical data:



Company name:

Created by:


Phone:

Date:





12/11/2020

Qty.	Description
	Motor type: MMS12000
	Rated power - P2: 170 kW
	Mains frequency: 50 Hz
	Rated voltage: 3 x 380-400-415 V
	Rated current: 350-345-350 A
	Cos phi - power factor: 0.88-0.85-0.81
	Rated speed: 2920-2920-2930 rpm
	Start. method: direct-on-line
	Enclosure class (IEC 34-5): IP68
	Built-in temp. transmitter: no
	Motor No: 96430683
	Windings: PVC
	Others:
	Net weight: 840 kg
	Shipping volume: 0.705 m ³


96431017 SP 360-4F G 50 Hz





Description	Value
General information:	
Product name:	SP 360-4F G
Product No:	96431017
EAN number:	5700393033528
Technical:	
Pump speed on which pump data are based:	2900 rpm
Rated flow:	360 m ³ /h
Rated head:	119 m
Stages:	4
Type of impeller:	F
Shaft seal for motor:	CER/CARBON
Curve tolerance:	ISO9906:2012 3B
Pump No:	96430919
Model:	A
Valve:	pump with built-in non-return valve
Motor version:	T30
Materials:	
Pump:	Cast iron
Pump:	EN-JL1040
Impeller:	Zinc-free bronze
Impeller:	DIN W.-Nr. 2.1050.01
Motor:	Cast iron
Motor:	DIN W.-Nr. 0.6025
Motor:	ASTM 35-40
Installation:	
Flange standard:	DIN
Pump outlet:	DN175
Motor diameter:	12 inch
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	40 °C
Max liquid t at 0.15 m/sec:	25 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Motor type:	MMS12000
Applic. motor:	GRUNDFOS
Rated power - P2:	170 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Rated current:	350-345-350 A
Cos phi - power factor:	0.88-0.85-0.81
Rated speed:	2920-2920-2930 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	no
Motor No:	96430683
Windings:	PVC
Others:	
Net weight:	840 kg
Shipping volume:	0.705 m ³



96431017 SP 360-4F G 50 Hz



96431017 SP 360-4F G 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96431017 SP 360-4F G 50 Hz



Note! All units are in [mm] unless others are stated.