

Qty. Description

1 SQ 3-105



Note! Product picture may differ from actual product

Product No.: [96510210](#)

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.

The motor is fitted with a replaceable end cover with socket.

Liquid:

Pumped liquid:	Water
Maximum liquid temperature:	35 °C
Max liquid t at 0.15 m/sec:	35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³

Technical:

Pump speed on which pump data are based:	10700 rpm
Rated flow:	3 m ³ /h
Rated head:	113 m
Approvals on motor nameplate:	CE,UL,CUL
Curve tolerance:	ISO9906:2012 3B

Materials:

Pump:	Polyamide / Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Polyamide
Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304

Installation:

Pump outlet:	Rp1 1/4
Minimum borehole diameter:	76 mm

Electrical data:

Motor type:	MS3
Power input - P1:	2.54 kW



Company name:

Created by:

Phone:

Date:

09/11/2020


Qty. Description

Rated power - P2: 1.85 kW
Power input P3: 1.74 kW
Mains frequency: 50 Hz
Rated voltage: 1 x 200-240 V
Rated current: 12.3 A
Power factor: 1.00
Rated speed: 10700 rpm
Start. method: direct-on-line
Enclosure class (IEC 34-5): IP68
Insulation class (IEC 85): F
Length of cable: 1.5 m
Motor No: 96160853





Others:

Net weight: 6.5 kg
Gross weight: 6.9 kg
Shipping volume: 0.011 m³
Danish VVS No.: 388433505
Country of origin: MX
Custom tariff no.: 84137029

96510210 SQ 3-105 50 Hz



Description	Value
General information:	
Product name:	SQ 3-105
Product No:	96510210
EAN number:	5700396504339
Price:	GBP 1604
Technical:	
Pump speed on which pump data are based:	10700 rpm
Rated flow:	3 m ³ /h
Rated head:	113 m
Stages:	8
Approvals on motor nameplate:	CE,UL,CUL
Curve tolerance:	ISO9906:2012 3B
Pump No:	96080410
Model:	B
Valve:	pump with built-in non-return valve
Materials:	
Pump:	Polyamide / Stainless steel
Pump:	DIN W.-Nr. 1.4301
Pump:	AISI 304
Impeller:	Polyamide
Motor:	Stainless steel
Motor:	DIN W.-Nr. 1.4301
Motor:	AISI 304
Installation:	
Pump outlet:	Rp1 1/4
Minimum borehole diameter:	76 mm
Liquid:	
Pumped liquid:	Water
Maximum liquid temperature:	35 °C
Max liquid t at 0.15 m/sec:	35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Motor type:	MS3
Power input - P1:	2.54 kW
Rated power - P2:	1.85 kW
Power input P3:	1.74 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 200-240 V
Rated current:	12.3 A
Power factor:	1.00
Rated speed:	10700 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	Y
Thermal protec:	internal
Length of cable:	1.5 m
Motor No:	96160853
Controls:	
CU 300/CU 301:	no communication possible
Others:	
Net weight:	6.5 kg
Gross weight:	6.9 kg
Shipping volume:	0.011 m ³
Sales region:	EU/S-AMREG/APREG
Danish VVS No.:	388433505





Company name:

Created by:


Phone:

Date:

09/11/2020


Description	Value
Country of origin:	MX
Custom tariff no.:	84137029

96510210 SQ 3-105 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

96510210 SQ 3-105 50 Hz



Note! All units are in [mm] unless others are stated.