

**Qty. Description**

1 SQ 7-15



**Note! Product picture may differ from actual product**

Product No.: [96510218](#)

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.

The motor is fitted with a replaceable end cover with socket.

**Liquid:**

Pumped liquid: Water  
 Maximum liquid temperature: 35 °C  
 Max liquid t at 0.15 m/sec: 35 °C  
 Selected liquid temperature: 20 °C  
 Density: 998.2 kg/m<sup>3</sup>

**Technical:**

Pump speed on which pump data are based: 10700 rpm  
 Rated flow: 7 m<sup>3</sup>/h  
 Rated head: 12 m  
 Approvals on motor nameplate: CE,UL,CUL  
 Curve tolerance: ISO9906:2012 3B

**Materials:**

Pump: Polyamide / Stainless steel  
 DIN W.-Nr. 1.4301  
 AISI 304  
 Impeller: Polyamide  
 Motor: Stainless steel  
 DIN W.-Nr. 1.4301  
 AISI 304

**Installation:**

Pump outlet: Rp1 1/2  
 Minimum borehole diameter: 76 mm

**Electrical data:**

Motor type: MS3  
 Power input - P1: 1.02 kW



Company name:

Created by:

Phone:

Date:

09/11/2020


**Qty. Description**

Rated power - P2: 0.7 kW  
Power input P3: 0.48 kW  
Mains frequency: 50 Hz  
Rated voltage: 1 x 200-240 V  
Rated current: 5.2 A  
Power factor: 1.00  
Rated speed: 10700 rpm  
Start. method: direct-on-line  
Enclosure class (IEC 34-5): IP68  
Insulation class (IEC 85): F  
Length of cable: 1.5 m  
Motor No: 96160850




Others:

Net weight: 4.7 kg  
Gross weight: 5.1 kg  
Shipping volume: 0.009 m<sup>3</sup>  
Danish VVS No.: 388437415  
Country of origin: DE  
Custom tariff no.: 84137029

## 96510218 SQ 7-15 50 Hz



Description	Value
<b>General information:</b>	
Product name:	SQ 7-15
Product No:	96510218
EAN number:	5700396504513
Price:	GBP 1194
<b>Technical:</b>	
Pump speed on which pump data are based:	10700 rpm
Rated flow:	7 m <sup>3</sup> /h
Rated head:	12 m
Stages:	1
Approvals on motor nameplate:	CE,UL,CUL
Curve tolerance:	ISO9906:2012 3B
Pump No:	96080390
Model:	B
Valve:	pump with built-in non-return valve
<b>Materials:</b>	
Pump:	Polyamide / Stainless steel
Pump:	DIN W.-Nr. 1.4301
Pump:	AISI 304
Impeller:	Polyamide
Motor:	Stainless steel
Motor:	DIN W.-Nr. 1.4301
Motor:	AISI 304
<b>Installation:</b>	
Pump outlet:	Rp1 1/2
Minimum borehole diameter:	76 mm
<b>Liquid:</b>	
Pumped liquid:	Water
Maximum liquid temperature:	35 °C
Max liquid t at 0.15 m/sec:	35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Motor type:	MS3
Power input - P1:	1.02 kW
Rated power - P2:	0.7 kW
Power input P3:	0.48 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 200-240 V
Rated current:	5.2 A
Power factor:	1.00
Rated speed:	10700 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	Y
Thermal protec:	internal
Length of cable:	1.5 m
Motor No:	96160850
<b>Controls:</b>	
CU 300/CU 301:	no communication possible
<b>Others:</b>	
Net weight:	4.7 kg
Gross weight:	5.1 kg
Shipping volume:	0.009 m <sup>3</sup>
Sales region:	EU/S-AMREG/APREG
Danish VVS No.:	388437415





Company name:


Created by:

Phone:

Date: 09/11/2020


Description	Value
Country of origin:	DE
Custom tariff no.:	84137029

**96510218 SQ 7-15 50 Hz**



Note! All units are in [mm] unless others are stated.  
Disclaimer: This simplified dimensional drawing does not show all details.

96510218 SQ 7-15 50 Hz



Note! All units are in [mm] unless others are stated.