

Company name: Created by: Phone:

Date: 24/12/2019

Qty. | Description

1 MAGNA3 32-80 N



Note! Product picture may differ from actual product

Product No.: 97924343

The Grundfos MAGNA3 is a circulator pump with permanent magnet motor that will fit both heating, cooling and domestic hot water circulation applications perfectly, making it the obvious choice for almost any building project – old or new.

With its unrivalled efficiency, all-encompassing range and built-in communication capabilities plus functionalities replacing system components, the MAGNA3 is ideal for building owners, engineers and specifiers looking to create high-performance systems for buildings.

The MAGNA3 is a canned-rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid.

The innovative clamp with only one screw enables easy repositioning of the pump head.


The MAGNA3 is a pump with no maintenance requirements and with extremely low Life Cycle Cost.



Company name: Created by: Phone:

Date: 24/12/2019

97924343 MAGNA3 32-80 N





Company name: Created by: Phone:

Date: 24/12/2019

Description	Value
General information:	
Product name:	MAGNA3 32-80 N
Product No:	97924343
EAN number:	5710626494194
	5710626494194
Price:	1.101,00 GBP
Technical:	
Rated flow:	5.6 m³/h
Rated head:	4.6 m
Head max:	80 dm
TF class:	110
Approvals on nameplate:	CE,VDE,EAC,CN ROHS,WEEE
Model:	D
Materials:	
Pump housing:	Stainless steel
	EN 1.4308
	ASTM 351 CF8
Impeller:	PES 30%GF
Installation:	
Range of ambient temperature:	0 40 °C
Maximum operating pressure:	10 bar
Pipe connection:	G 2"
Pressure rating:	PN10
Port-to-port length:	180 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-10 110 °C
Selected liquid temperature:	60 °C
Density at selected liquid temperature:	983.2 kg/m³
Electrical data:	
Power input - P1:	9 136 W
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 230 V
Maximum current consumption:	0.09 1.19 A
Enclosure class (IEC 34-5):	X4D
Insulation class (IEC 85):	F
Others:	
Energy (EEI):	0.18
Net weight:	4.8 kg
Gross weight:	5.27 kg
Shipping volume:	0.015 m ³
Danish VVS No.:	380796080
Swedish RSK No.:	5803241
	4615647
FINNISN I VI INO.:	
Finnish LVI No.: Country of origin:	DE

