

Qty. Description

1 GT-U+ 2000 PN10



Note! Product picture may differ from actual product

Product No.: [99082704](#)

Grundfos GT-U+ 2000 PN10 is a Bladder pressure tank, with a capacity of 2000.0 l and Vertical installation. The tanks are approved for drinking water. The GT-U+ 2000 PN10 is designed for a maximum operation pressure of 10 bar and a maximum liquid temperature of 90 °C.

The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.

The tank has a FlowThru connection, which constantly flushes the tank while the pump is running.

This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.

The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.

The tank has a FlowThru connection, which constantly flushes the tank while the pump is running.

This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.

The tanks have a non-replaceable diaphragm that is pre-charged with nitrogen (1.5 bar).

The tanks have a non-toxic butyl rubber diaphragm, dividing the tank chamber into two compartments.

The upper compartment contains compressed nitrogen.

The lower compartment has a liner of polypropylene (PP) and is filled with water from the pump.

A pressure tank ensures controlled pressure in the water supply and thereby limits the switching frequency of the pump in case of low water consumption or leakage loss.

The result is increased comfort in your installation by limiting the start/stop frequency of your pump, and it increases system comfort by compensating for pressure drops when a tap is opened, while reducing problems with water hammer in the pipework.

Liquid:

Liquid max temp: 90 °C

Technical:

Membrane type: Bladder

Materials:



Company name:

Created by:


Phone:

Date:


14/10/2021

Qty.	Description
	<p data-bbox="199 338 703 367">Basic: Carbon steel</p> <p data-bbox="199 398 328 427">Installation:</p> <p data-bbox="199 427 638 456">Maximum operating pressure: 10 bar</p> <p data-bbox="199 456 587 486">Type of connection: G</p> <p data-bbox="199 486 635 515">Size of connection: 2 inch</p> <p data-bbox="199 515 643 544">Size: 2000.0</p> <p data-bbox="199 575 284 604">Others:</p> <p data-bbox="199 604 639 633">Net weight: 360 kg</p> <p data-bbox="199 633 639 663">Gross weight: 383 kg</p> <p data-bbox="199 663 667 692">Applicat. typ: Standard</p> <p data-bbox="199 692 603 721">Country of origin: CN</p> <p data-bbox="199 721 676 750">Custom tariff no.: 73102990</p>

Description	Value
General information:	
Product name:	GT-U+ 2000 PN10
Product No:	99082704
EAN number:	5712606401666
Price:	GBP 7305
Technical:	
Membrane type:	Bladder
Materials:	
Basic:	Carbon steel
Installation:	
Maximum operating pressure:	10 bar
Pre-pressure:	4 bar
Type of connection:	G
Size of connection:	2 inch
Installation:	Vertical
Size:	2000.0
Liquid:	
Liquid max temp:	90 °C
Others:	
Net weight:	360 kg
Gross weight:	383 kg
Applicat. typ:	Standard
Country of origin:	CN
Custom tariff no.:	73102990



99082704 GT-U+ 2000 PN10



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.