

Customer	Date	12/9/2020
Contact	Project	
Phone number	Project no.	
Email		

ESHE 40-125/22/P25RSSA

101860280

Operating data

Pump type	Single head pump	Fluid	Water, pure
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	l/s 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	l/s ()
Speed	rpm 2900	Flow Max-	l/s 12.5
Number of stages	1	Min-	l/s 5
Max. casing pressure	kPa	Nominal	m
Max. working pressure	kPa 230	Head at Qmax	m 10.2
Head H(Q=0)	m 23	at Qmin	m 21.1
Weight	kg	Shaft power	kW ()
	Max. mm 133	Max. shaft power	kW 2.1
Impeller R	designed mm 133	Efficiency	%
	Min. mm 112	NPSH 3%	m
Suction nozzle	DN 65 PN 12 EN1092-2 (e-SH)	Discharge nozzle	DN 40 PN 12 EN1092-2 (e-SH)

Pump Materials

Pump body	Stainless steel / AISI 316L
Impeller	Stainless steel / AISI 316L
SEAL HOUSING	Stainless steel / AISI 316L
Wear Ring	Stainless steel / AISI 316L
Counterwear ring	Stainless steel / AISI 316L
Shaft extension	Stainless steel / AISI 316L
Rigid shaft coupling	Stainless steel / AISI 316
Impeller locknut and washer	Stainless steel / AISI 316
Tab	Stainless steel / AISI 316L

Shaft Seal

Single Seal	
e-SH - uniten	Roten
Rotating Assembly	V-Ceramic
Fixed Assembly	B-Resin impregnated carbon
Elastomers	V-FKM (FPM)
Springs	G-AISI 316
Other Components	G-AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	400 V
Specific design	IE3 Three phase surface motor		
Type	PLM90.../322 E3		
Rated power	2.2 kW	Electric current	4.56 A
Speed	2885 rpm	Degree of protection	IP 55
Frame size	90	Weight	18 kg
Shaft diameter	0 mm	Colour	RAL 5010
Insulation class	F		

Coupling

Manufacturer	
Series	
Type	
Frame size	
Spacer length	
Weight	
Coupling protection	

Base plate

Description	
Weight	

Remarks:

Customer	Date	12/9/2020
Contact	Project	
Phone number	Project no.	
Email		


ESHE 40-125/22/P25RSSA

101860280

Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 l/s	Flow		Impeller R	133 mm
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,4		Speed	2900 rpm

Power data referred to:
 Water, pure [100%] ; 4°C; 1000kg/m³; 1.57mm²/s
 Performance according to ISO 9906:2012 – Grade 3B



Customer	Date	12/9/2020
Contact	Project	
Phone number	Project no.	
Email		

ESHE 40-125/22/P25RSSA
101860280

Dimensions mm/l

a	80		
B	218		
DNA	65		
DNM	40		
h1	112		
h2	140		
Hmax	252		
k	100		
L	478		
n	190		
n1	130		
x	134		
		Total weight	30 kg

Connections mm

Suction nozzle	Discharge nozzle
DN 65	DN 40
PN 12	PN 12
EN1092-2 (e-SH)	EN1092-2 (e-SH)

D	185	D	150
Dia. Holes	18	Dia. Holes	18
DN	65	DN	40
G	104	G	68
M	145	M	110
Max thickness	18	Max thickness	16
N° Holes	4	N° Holes	4

Drawing

