

## HVAC Flanged Rubber Bellows Untied

### Specification

Commercial quality EPDM bellows intended primarily for HVAC water applications – LT heating, waste, sanitary, chilled.

**Not suitable for** drinking water, contaminated water or mineral oil products.

### Materials

- Liner EPDM
- Reinforcement Nylon chord
- Cover EPDM
- Flanges Carbon steel, galvanised PN16

### Rating

16 Barg @ 20°C to 6 Barg @ 95°C.  
Vacuum rating 400 mmHg.



Size	Length	Axial Comp.	Axial Ext.	Lateral	Angular	Stock code
in.	mm	mm	mm	mm	degree	
DN032-1¼"	106	20	20	±30	± 7.5	R0032SF5AA16U
DN032-1¼"	130	30	20	±20	± 35	R0032SF15A16U
DN032-1¼"	150	12	9	±12	± 15	R0032SF10B16U
DN040-1½"	106	20	20	±30	± 7.5	R0040SF5AA16U
DN040-1½"	130	30	20	±20	± 35	R0040SF15A16U
DN040-1½"	150	12	9	±12	± 15	R0040SF10B16U
DN050-2"	106	20	20	±30	± 7.5	R0050SF5AA16U
DN050-2"	130	30	20	±20	± 35	R0050SF15A16U
DN050-2"	150	12	9	±12	± 15	R0050SF10B16U
DN065-2½"	106	20	20	±30	± 7.5	R0065SF5AA16U
DN065-2½"	130	30	20	±20	± 30	R0065SF15A16U
DN065-2½"	150	12	9	±12	± 15	R0065SF10B16U
DN080-3"	106	20	20	±30	± 7.5	R0080SF5AA16U
DN080-3"	130	30	20	±20	± 30	R0080SF15A16U
DN080-3"	150	12	9	±12	± 15	R0080SF10B16U
DN100-4"	106	20	20	±30	± 7.5	R0100SF5AA16U
DN100-4"	130	30	20	±20	± 25	R0100SF15A16U
DN100-4"	150	16	9	±12	± 15	R0100SF10B16U
DN125-5"	106	20	20	±30	± 7.5	R0125SF5AA16U
DN125-5"	130	30	20	±20	± 25	R0125SF15A16U
DN125-5"	150	16	9	±12	± 15	R0125SF10B16U
DN150-6"	106	20	20	±30	± 7.5	R0150SF5AA16U
DN150-6"	130	30	20	±20	± 15	R0150SF15A16U
DN150-6"	150	16	9	±12	± 15	R0150SF10B16U
DN200-8"	106	20	20	±30	± 5	R0200SF5AA16U
DN200-8"	130	30	20	±20	± 15	R0200SF15A16U
DN200-8"	150	16	9	±12	± 15	R0200SF10B16U
DN250-10"	106	20	20	±30	± 5	R0250SF5AA16U
DN250-10"	130	30	20	±20	± 10	R0250SF15A16U
DN250-10"	200	19	19	±19	± 15	R0250SF10E16U

Movements are non concurrent

### Product by FlexEJ Ltd

For technical assistance & sales  
t: +44 (0)1384 881188  
e: sales@flexej.co.uk

## HVAC Flanged Rubber Bellows

### Tied

#### Specification

Commercial quality EPDM bellows intended primarily for HVAC water applications – LT heating, waste, sanitary, chilled.

**Not suitable for** drinking water, contaminated water or mineral oil products.

#### Materials

- Liner EPDM
- Reinforcement Nylon chord
- Cover EPDM
- Flanges Carbon steel, galvanised PN16

#### Rating

16 Barg @ 20°C to 6 Barg @ 95°C.  
Vacuum rating 400 mmHg.



Size	Length	Axial Comp.	Axial Ext.	Lateral	Angular	Stock code
in.	mm	mm	mm	mm	degree	
DN032-1¼"	106	20	20	±30	± 7.5	R0032SF5AA16T
DN032-1¼"	130	30	20	±20	± 35	R0032SF15A16T
DN032-1¼"	150	12	9	±12	± 15	R0032SF10B16T
DN040-1½"	106	20	20	±30	± 7.5	R0040SF5AA16T
DN040-1½"	130	30	20	±20	± 35	R0040SF15A16T
DN040-1½"	150	12	9	±12	± 15	R0040SF10B16T
DN050-2"	106	20	20	±30	± 7.5	R0050SF5AA16T
DN050-2"	130	30	20	±20	± 35	R0050SF15A16T
DN050-2"	150	12	9	±12	± 15	R0050SF10B16T
DN065-2½"	106	20	20	±30	± 7.5	R0065SF5AA16T
DN065-2½"	130	30	20	±20	± 30	R0065SF15A16T
DN065-2½"	150	12	9	±12	± 15	R0065SF10B16T
DN080-3"	106	20	20	±30	± 7.5	R0080SF5AA16T
DN080-3"	130	30	20	±20	± 30	R0080SF15A16T
DN080-3"	150	12	9	±12	± 15	R0080SF10B16T
DN100-4"	106	20	20	±30	± 7.5	R0100SF5AA16T
DN100-4"	130	30	20	±20	± 25	R0100SF15A16T
DN100-4"	150	16	9	±12	± 15	R0100SF10B16T
DN125-5"	106	20	20	±30	± 7.5	R0125SF5AA16T
DN125-5"	130	30	20	±20	± 25	R0125SF15A16T
DN125-5"	150	16	9	±12	± 15	R0125SF10B16T
DN150-6"	106	20	20	±30	± 7.5	R0150SF5AA16T
DN150-6"	130	30	20	±20	± 15	R0150SF15A16T
DN150-6"	150	16	9	±12	± 15	R0150SF10B16T
DN200-8"	106	20	20	±30	± 5	R0200SF5AA16T
DN200-8"	130	30	20	±20	± 15	R0200SF15A16T
DN200-8"	150	16	9	±12	± 15	R0200SF10B16T
DN250-10"	106	20	20	±30	± 5	R0250SF5AA16T
DN250-10"	130	30	20	±20	± 10	R0250SF15A16T
DN250-10"	200	19	19	±19	± 15	R0250SF10E16T

Movements are non concurrent

#### Product by FlexEJ Ltd

For technical assistance & sales  
t: +44 (0)1384 881188  
e: sales@flexej.co.uk