GRUNDFOS

Company name:
Created by:
Phone:

Date: 26/10/2026

Qty.	Description
1	**SQE 7-15**



Note! Product picture may differ from actual product

Product No.: 96510169

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.
The motor is fitted with a replaceable end cover with socket.

Liquid:

Pumped liquid:	Water
Liquid temperature range:	0 .. 35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³

Technical:

Pump speed on which pump data are based:	10700 rpm
Rated flow:	7 m³/h
Rated head:	12 m
Approvals:	CE,PCBC,RCM,EAC,CN Rohs Exempt,Morocco,UKCA,SEPRO
Curve tolerance:	ISO9906:2012 3B

Materials:

Pump:	Stainless steel
	EN 1.4301
	AISI 304
Impeller:	Composite
	ZYTEL 70G30 HSLR PA6.6-GF30
Motor:	Stainless steel
	EN 1.4301
	AISI 304

Installation:

Maximum operating pressure:	15 bar
Pump outlet:	RP1 1/2
Minimum borehole diameter:	76 mm

GRUNDFOS

Company name:
Created by:
Phone:

Date: 26/10/2026

Qty.	Description	
1	Electrical data:	
	Motor type:	MSE3
	Power input - P1:	1 kW
	Rated power - P2:	0.7 kW
	Power (P2) required by pump:	0.48 kW
	Mains frequency:	50 Hz
	Rated voltage:	1 x 200-240 V
	Rated current:	5.3 A
	Power factor:	1.00
	Rated speed:	10700 rpm
	Start. method:	direct-on-line
	Enclosure class (IEC 34-5):	IP68
	Insulation class (IEC 85):	F
	Built-in motor protection:	YES
		Y
	Thermal protection:	12
	Length of cable:	1.5 m
	Motor No:	96160854
	Others:	
	Net weight:	4.42 kg
	Gross weight:	5.14 kg
	Shipping volume:	0.0092 m³
	Danish VVS No.:	388447415
	Swedish RSK No.:	5853388


Company name:

Created by:

Phone:

Date: 26/10/2026

Description	Value
General information:	
Product name:	SQE 7-15
Product No:	96510169
EAN number:	5700396502786
Price:	GBP 1951
Technical:	
Pump speed on which pump data are based:	10700 rpm
Rated flow:	7 m³/h
Rated head:	12 m
Stages:	1
Approvals:	CE,PCBC,RCM,EAC,CN Rohs Exempt,Morocco,UKCA,SEPRO
Curve tolerance:	ISO9906:2012 3B
Pump No:	96080390
Model:	C
Valve:	pump with built-in non-return valve
Materials:	
Pump:	Stainless steel
	EN 1.4301
	AISI 304
Impeller:	Composite
	ZYTEL 70G30 HSLR PA6.6-GF30
Motor:	Stainless steel
	EN 1.4301
	AISI 304
Installation:	
Maximum operating pressure:	15 bar
Pump outlet:	RP1 1/2
Minimum borehole diameter:	76 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	MSE3
Power input - P1:	1 kW
Rated power - P2:	0.7 kW
Power (P2) required by pump:	0.48 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 200-240 V
Rated current:	5.3 A
Power factor:	1.00
Rated speed:	10700 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	YES
	Y
Thermal protec:	internal
Thermal protection:	12
Length of cable:	1.5 m
Motor No:	96160854
Controls:	



Pumped liquid = Water
Liquid temperature during operation = 20 °C
Density = 998.2 kg/m³

GRUNDFOS

Company name:
Created by:
Phone:

Date: 26/10/2026


Description	Value
CU 300/CU 301:	communication with CU 300/CU 301 possible
Others:	
Net weight:	4.42 kg
Gross weight:	5.14 kg
Shipping volume:	0.0092 m³
Sales region:	EU/S-AMREG/APREG
Danish VVS No.:	388447415
Swedish RSK No.:	5853388

GRUNDFOS

Company name:
Created by:
Phone:

Date: 26/10/2026

96510169 SQE 7-15 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

GRUNDFOS

Company name:
Created by:
Phone:

Date: 26/10/2026