



Data sheet

Hydraulic data

Minimum efficiency index (MEI)	≥0,4
Min. fluid temperature $T_{\min}$	-20 °C
Max. fluid temperature $T_{\max}$	140 °C
Max. ambient temperature $T_{\max}$	40 °C
Maximum operating pressure P_N	16 bar
Note on dimensioning	16 bar to 120 °C, 13 bar to 140 °C

Motor data

Mains connection	3~400 V, 50 Hz
Number of poles	4
Voltage tolerance	±10 %
Motor efficiency class	IE3
Rated power P_2	2,2 kW
Rated current I_N	5,4 A
Rated speed n	1450 1/min
Power factor $\cos \varphi_{100}$	0,69
Motor efficiency 50% $\eta_M 50\%$	81,5 %
Motor efficiency 75% $\eta_M 75\%$	84,8 %
Motor efficiency 100% $\eta_M 100\%$	86,7 %
Insulation class	F
Protection class motor	IP55
Motor protection	no


Materials

Pump housing	5.1301/EN-GJL-250 KTL-coated
Impeller	Grey cast iron EN-GJL-200
Shaft	Stainless steel
Mechanical seal	AQ1EGG
Lantern	5.1301/EN-GJL-250 KTL-coated

Installation dimensions

Pipe connection on the suction side DN_s	DN 50
Pipe connection on the discharge side DN_d	DN 50
Port-to-port length L_0	440 mm


Pump curves




Fluid media	Water 100 %
Fluid temperature	20.00 °C
speed at duty point	1,453 1/min
Impeller diameter	207 mm

Dimensions and dimensions drawings

Atmos GIGA-I 50/200-2,2/4



Wiring diagram



Δ: Connection diagram delta connection

Y: Connection diagram star connection

Motor protection switch required on-site. Check the direction of rotation! To change the direction of rotation, exchange any two phases.

$P_2 \leq 3 \text{ kW}$ 3~400 V Y

3~230 V Δ

$P_2 \geq 4 \text{ kW}$ 3~690 V Y

3~400 V Δ

After removing the bridges, Y-Δ start is possible.