

For sealed heating installations (acc. to EN12828) and chilled water (cooling) installations.






Advantages

- Nitrogen gas filling for longer maintenance of pre-pressure.
- Each vessel is factory tested.
- Diaphragm: Flexible rubber with rolling action.

Technical Specifications

- Maximum working pressure: 6.0 bar.
- Vessels in accordance with EN13831.
- Suitable for systems with a maximum system temperature of 120 °C.
- Min./ max. temperature diaphragm: -10 / 70 °C.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- All welded construction.
- In accordance with Pressure Equipment Directive 2014/68/EU.
- Tilting height:
800L: 1865 mm.
1000L: 2195 mm.
- Red (RAL 3002) epoxy powder coating.



Type	Capacity [l]	Pre-charge [bar]	Dimensions				Syst. conn. (D)	Weight [kg]		Order Code
			Ø A [mm]	B [mm]	Ø C [mm]	E [mm]				
Contraflex 100/1.5 [6bar]	100	1.5	550	630	440	63	G $\frac{3}{4}$ " M	13.9	8	26103
Contraflex 150/1.5 [6bar]	150	1.5	550	837	440	63	G $\frac{3}{4}$ " M	17.6	8	16153
Contraflex 200/1.5 [6bar]	200	1.5	484	1300	360	-	R 1"	25.0	8	26213
Contraflex 250/1.5 [6bar]	250	1.5	600	1153	450	-	R 1"	31.8	6	16253
Contraflex 300/1.5 [6bar]	300	1.5	600	1330	450	-	R 1"	35.6	6	26303
Contraflex 400/1.5 [6bar]	400	1.5	790	1180	610	-	R 1"	53.4	1	26413
Contraflex 500/1.5 [6bar]	500	1.5	790	1330	610	-	R 1"	60.2	1	26523
Contraflex 600/1.5 [6bar]	600	1.5	790	1538	610	-	R 1"	67.0	1	17162
Contraflex 800/1.5 [6bar]	800	1.5	790	1888	610	-	R 1"	84.2	1	17181
Contraflex 1000/1.5 [6bar]	1000	1.5	790	2268	610	-	R 1"	95.0	1	17190



Find more information online:

[Installation and operating instruction](#)

[EU Declaration of conformity PED Module D1](#)

[EU Declaration of conformity PED Module B+D Cat. III](#)

[EU Declaration of conformity PED Module B+D Cat. IV](#)

[Declaration of conformity UKCA](#)

[Contraflex DWG](#)

[Contraflex RFA](#)

[Contraflex STEP](#)

[Packaging data](#)

Washway Lane
UK-WA10 6PB, St Helens, Merseyside - gb

I flamco.aalberts-hfc.com/uk-en