

WaterBoost



AWB-250LV

250 Litre Vertical Accumulator Vessel

Part No. AWB-250LV



WhatsApp

07464 644 830

waterboost.co.uk

sales@waterboost.co.uk

250 litre

Storage capacity

150 litre

Working capacity

10 bar

Max working pressure

90°C

Max temperature

1¼" BSP

Connection size

5 yr

Warranty

OVERVIEW

The WaterBoost AWB-250LV is a 250 litre vertical accumulator vessel designed to store pressurised water and deliver it on demand, significantly improving flow rates to taps, showers, baths and appliances. It uses a patented CAD-2 diaphragm technology for superior air and water separation, condensation-reducing design, and a non-corrosive water chamber — making it ideal for domestic and light commercial boosting systems.

KEY FEATURES

- Patented CAD-2 diaphragm technology
- 100% butyl diaphragm — chlorine resistant
- Virgin polypropylene liner — true non-corrosive chamber
- Condensation-reducing design
- Stainless steel 1¼" BSP water connection
- O-ring sealed, leak-free air valve cap
- Two-part polyurethane, epoxy-primed paint finish
- WRAS, CE/PED, ACS, ISO-9001 approved
- No maintenance required
- 5 year warranty

WHAT'S INCLUDED

- Vessel:** 250 litre vertical accumulator vessel
- Fittings:** 1¼" BSP stainless steel connection elbow
- Air valve:** O-ring sealed, leak-free Schrader valve cap

IDEAL FOR


- Properties with low mains flow — 1 to 3 bedroom homes
- Use alongside the WaterBoost ACF1 booster pump for best performance
- Whole-house flow improvement without boosting pressure
- Reducing pump cycling and extending pump life
- Combination boilers, unvented cylinders, showers and taps

TECHNICAL SPECIFICATIONS

Model	AWB-250LV
Nominal volume	250 litres
Style	Vertical / upright
Diaphragm	CAD-2 patented butyl
Liner	Virgin polypropylene
Shell	Carbon steel
Paint finish	2-part polyurethane / epoxy
Connection	1¼" BSP stainless steel
Max working pressure	10 bar
Max temperature	90°C
Height (A)	1227 mm
Diameter (B)	534 mm
Base diameter (D)	446 mm
Shipping weight	39.24 kg
Approval	WRAS, CE/PED, ACS, ISO-9001
Warranty	5 years



HOW IT WORKS



- 1 Mains water fills the accumulator vessel under resting (static) pressure
- 2 When a tap or outlet opens, pressurised water is released instantly from the vessel
- 3 The vessel delivers a full-flow burst before returning to mains supply
- 4 For best results, pair with the WaterBoost ACF1 pump to pre-charge above mains pressure

SIZING GUIDE

1–2 bedroom home	60 L, 100 L or 200 L	2–3 bedroom home	200 L, 250 L or 300 L
3+ bedrooms	300 L or 450 L	Usable volume rule	Vessel size × 0.6 = usable litres
Example (AWB-250LV)	250 × 0.6 = 150 L usable	Average shower flow	10–12 L/min

PRE-CHARGE PRESSURE GUIDE



Mains pressure	Air charge (65%)
2.0 bar (30 psi)	1.3 bar
3.0 bar (44 psi)	1.95 bar
3.5 bar (51 psi)	2.275 bar
4.0 bar (58 psi)	2.6 bar
4.5 bar (65 psi)	2.925 bar
5.0 bar (72 psi)	3.25 bar

Set air charge = mains pressure × 0.65





DIMENSIONS

Size	A (Height)	B (Diameter)	D (Base Ø)	Connection	Max Pressure
60 L	572 mm	407 mm	367 mm	1" BSP	10 bar
80 L	752 mm	407 mm	367 mm	1" BSP	10 bar
100 L	897 mm	407 mm	367 mm	1" BSP	10 bar
130 L	1109 mm	407 mm	367 mm	1" BSP	10 bar
200 L	1055 mm	532 mm	446 mm	1¼" BSP	10 bar
250 L	1227 mm	534 mm	446 mm	1¼" BSP	10 bar
300 L	1512 mm	534 mm	446 mm	1¼" BSP	10 bar
325 L	1166 mm	662 mm	542 mm	1¼" BSP	10 bar
450 L	1551 mm	662 mm	542 mm	1¼" BSP	10 bar

★ Highlighted row = AWB-250LV (this product). All sizes available at waterboost.co.uk

