



WaterBoost

WB – Grand 2000

High-capacity boosted water storage

Part No. **2702G410**

Get in touch



WhatsApp

07464 644 830

waterboost.co.uk
anglianpumping.com

IN STOCK · FAST DISPATCH

Serious storage. Slimline footprint.

The WaterBoost Grand 2000 combines a 2,000-litre Enduramaxx slimline tank with a DAB Esybox Twin variable-speed pump set. A single-tank design — no linking pipework, no matched-pair delivery — giving genuine high-capacity storage in a footprint just 850 mm wide. Two DAB e.sybox units run in wireless duty/standby, alternating priority every 23 hours, with full pump redundancy if one unit fails.



2,000 L

Stored volume

140 L/min

Combined @ 3 bar

6.5 bar

Max pressure

1985×850×1971

L×W×H (mm)

10 yr

Tank warranty

KEY FEATURES

- Single-tank design — no cross-linking pipework required
- Narrow 850 mm profile — sits along wall or side passage
- Twin-pump duty/standby — 140 l/min combined @ 3 bar
- Intelligent variable-speed pump — adjusts to demand
- Energy-efficient — up to 50% saving vs fixed-speed
- Ultra quiet — 43 dB(A) at 1m
- True redundancy — continuous supply if one pump fails
- Anti-stagnation — pump priority rotates every 23 hours
- DAB DConnect Wi-Fi, Google Home & Alexa compatible
- UK-manufactured Enduramaxx tank, Italian-manufactured DAB pumps

WHAT'S INCLUDED

Tank

1 × Enduramaxx 2,000 L slimline (1SG)

Pumps

1 × DAB Esybox Twin variable-speed set

Frame

Stainless steel twin-pump mounting frame

Suction

Tank-to-pump suction line with flex connectors

Valves

¾" ball float valve (pre-fitted)

Byelaw

Byelaw fittings and screened overflow

IDEAL FOR

- Multi-bathroom homes (4–6 bathrooms)
- Properties with restricted plant room access
- Rural / low mains pressure sites
- Light commercial premises
- Backup & resilience against mains interruption

TANK — Enduramaxx 2000 L Slimline (1SG)

Nominal capacity	2,000 litres (±3%)
Material	Polyethylene, UK manufactured
Construction	Rotationally moulded slimline
Colour	Blue
Dimensions (L×W×H)	1985 × 850 × 1971 mm
Outlet	1.5" BSP (standard)
Lid	Ø 455 mm vented
Overflow	Moulded overflow hoods
Weight (full)	~2,050 kg
Warranty	10 years

PUMP SET — DAB Eskybox Twin Variable Speed

Model	DAB Eskybox Twin
Configuration	Duty / Standby
No. of pumps	2
Max flow rate	140 L/min @ 3 bar (combined)
Max pressure	6.5 bar (65 m head)
Motor (per unit)	1.55 kW / 2 HP
Voltage	230V 1φ 50 Hz
Noise level	43 dB(A) per pump at 1m
Speed control	Fully automatic variable
Display	Colour LCD touchscreen (each)
Connectivity	Wi-Fi, H2D, DConnect, Google, Alexa
Warranty (each)	3 years


SYSTEM OVERVIEW

Part number	2702G410
Availability	In stock — ships same or next working day
Total footprint (tank only)	1985 × 850 × 1971 mm
Access opening required	900 mm minimum
Base loading (full)	~2,050 kg — level base pad required
Interconnecting pipework	Included as standard
Combined warranty	Tank 10 years · Pumps 3 years each
Supplied by	Anglian Pumping Services — established 1975

HOW IT WORKS

- 1 Mains water fills the tank via the pre-fitted float valve.
- 2 Tank buffers demand — smoothing slow-fill mains or borehole yield.
- 3 DAB Eskybox Twin draws from tank outlet and boosts to system pressure.
- 4 Second pump starts on demand; alternates priority every 23 hours.

PERFORMANCE CURVE — DAB Eskybox Twin



Established 1975

In stock

Fast dispatch