



WaterBoost

ATX-200H Horizontal

Horizontal mains pressure booster — 200 L accumulator & variable speed pump

Part No. ATX-200H

Get in touch



WhatsApp
07464 644 830

waterboost.co.uk
anglianpumping.com

IN STOCK · FAST DISPATCH

Whole-house pressure. Lies down to fit.

The WaterBoost ATX-200H is a horizontal integrated accumulator booster for lofts, eaves, under-bath voids and low cupboards. A 200 litre sealed WRAS-approved vessel on its side with a variable speed pump beside or in front, connected directly to the mains. Up to 45 L/min peak, 22 L/min at 3.2 bar for up to 11 minutes, 532 mm high. No break tank, no overflow, two water connections.



200 L

Accumulator · 120 L useable

45 L/min

Peak flow

22 L/min

@ 3.2 bar · up to 11 min

532 mm

Height (plus feet)

5 yr

Tank warranty

KEY FEATURES

- Horizontal — 532 mm high, fits lofts, eaves and under-bath voids
- Direct to mains: no break tank, no overflow, two connections
- Fully sealed vessel — zero air contact, no hygiene maintenance
- Variable-speed inverter — only boosts the shortfall
- Instant 22 L/min burst from stored volume, 12 L/min continuous
- QuietPad anti-vibration base under the pump as standard
- 30-second pump swap — 2-clip dock and built-in bypass
- Dry run protection and anti-seize exercise function
- 40 dB(A) · WiFi via DConnect app

WHAT'S INCLUDED

Vessel

200 L horizontal accumulator, WRAS approved, on saddle feet

Pump

Variable speed inverter booster pump

Base

WaterBoost QuietPad anti-vibration pump base

Dock

ATX 2-clip dock with mains bypass

Pipework

Flexible connections, vessel to pump

Fittings

2 × ¾" BSP multi-directional connections

IDEAL FOR

- Lofts, roof spaces and eaves cupboards
- Under-bath and under-floor voids
- 2–4 bed homes, combi boilers, unvented cylinders
- Homes with floor space but no headroom

VESSEL — 200 L horizontal accumulator	
Capacity	200 litres · 120 litres useable
Approval	WRAS approved
Type	Sealed, pressurised — no air contact
Orientation	Horizontal on saddle feet
Length	1,326 mm
Diameter / height	532 mm (plus feet)
Connections	2 × ¾" BSP male, multi-directional
Overflow	Not required
Warranty	5 years

PUMP — Variable speed	
Type	Variable speed inverter
Peak burst flow	Up to 45 L/min
Sustained	22 L/min at 3.2 bar, up to 11 min
Continuous	12 L/min at 3 bar
Noise	40 dB(A)
Mounting	QuietPad anti-vibration base, 2-clip dock
Protection	Dry run · anti-seize exercise
Connectivity	WiFi — DConnect app + HMI
Approval	WRAS approved
Warranty	3 years

SYSTEM OVERVIEW	
Part number	ATX-200H
Availability	In stock — ships same or next working day
Footprint	Pump beside: 1,458 × 532 mm · pump in front: 1,326 × 751 mm
Weight	~45 kg empty · ~245 kg filled — confirm joist loading for lofts
Suited to	2–4 bed homes · one bathroom in regular use · combi & unvented
Combined warranty	Tank 5 years · Pump 3 years
Supplied by	Anglian Pumping Services — established 1975

HOW IT WORKS

- 1 Mains pressure charges the sealed 200 L vessel; 120 L is held ready under pressure
- 2 Open a tap and the stored volume delivers an instant boost — 22 L/min at 3.2 bar for up to 11 min
- 3 The variable speed pump measures incoming pressure and adds only the shortfall to your set point
- 4 Stored volume used? Boosting continues at 12 L/min at 3 bar; the vessel recharges when demand stops

Specification notes. Direct-mains system — continuous flow after discharge is limited to 12 L/min under the Water Fittings Regulations. Loft installs: check the 532 mm diameter against the hatch and spread the filled weight across joists. Two bathrooms at once? See the ATX-250H or ATX-300H.

TWO-PHASE OPERATION

Phase 1 — stored	22 L/min @ 3.2 bar
Duration	Up to 11 min
Peak burst	Up to 45 L/min
Phase 2 — continuous	12 L/min @ 3 bar
Recharge	Automatic on demand stop
Flow rates depend on incoming mains supply	

Established 1975
In stock
Fast dispatch