



WaterBoost

ATX-300H 4.5 Horizontal

Horizontal mains pressure booster — 300 L accumulator & WB-Compact 4.5 pump

Part No. ATX-300H 4.5

Get in touch



WhatsApp
07464 644 830

waterboost.co.uk
anglianpumping.com

IN STOCK · FAST DISPATCH

Two or more showers at 4.5 bar. Lies down to fit.

The WaterBoost ATX-300H 4.5 is the largest high-pressure horizontal model in the ATX range, for lofts, eaves, under-bath voids and low cupboards. A 300 litre sealed WRAS-approved vessel on its side with the WB-Compact 4.5 variable speed pump beside or in front, connected directly to the mains and charged up to 4.5 bar. Up to 80 L/min peak, 27 L/min at up to 4.5 bar for up to 11 minutes, then 12 L/min at 3.0 bar continuous. Two or more showers running at once.



4.5 bar

Max pressure

300 L

Accumulator · 180 L useable

80 L/min

Peak flow

27 L/min

@ 4.5 bar · up to 11 min

5 yr

Tank warranty

KEY FEATURES

- Horizontal — low profile, fits lofts, eaves and under-bath voids
- Charged up to 4.5 bar — rain heads, top floors, unvented cylinders
- Direct to mains: no break tank, no overflow, two connections
- Fully sealed vessel — zero air contact, no hygiene maintenance
- Variable-speed inverter — only boosts the shortfall
- Instant 27 L/min from stored volume, 12 L/min at 3.0 bar continuous
- QuietPad anti-vibration base under the pump as standard
- 30-second pump swap — 2-clip dock and full-bore bypass
- 40 dB(A) · WiFi via the DAB H2D app · Power Shower mode

WHAT'S INCLUDED

Vessel

300 L horizontal accumulator, WRAS approved, on saddle feet

Pump

WaterBoost WB-Compact 4.5 (ACM) variable speed booster

Base

WaterBoost QuietPad anti-vibration pump base

Dock

ATX 2-clip dock with mains bypass

Pipework

Flexible connections, vessel to pump

Fittings

2 × 1" BSP multi-directional connections

IDEAL FOR

- Lofts, roof spaces and eaves cupboards
- Top-floor bathrooms, rain heads and body jets
- Unvented cylinders needing more than 3 bar
- Homes with floor space but no headroom

VESSEL — 300 L horizontal accumulator	
Capacity	300 litres · 180 litres useable
Approval	WRAS approved
Type	Sealed, pressurised — no air contact
Orientation	Horizontal on saddle feet
Working pressure	Charged up to 4.5 bar
Pre-charge	Factory set
Connections	2 × 1" BSP, multi-directional
Overflow	Not required
Warranty	5 years

PUMP — WB-Compact 4.5	
Model	WB-Compact 4.5 (ACM series)
Type	Variable speed inverter
Max pressure	4.5 bar
Real-world output	12 L/min at 3.0 bar
Noise	40 dB(A)
Dimensions	439 × 263 × 236 mm
Mounting	QuietPad anti-vibration base, 2-clip dock
Connectivity	WiFi — DAB H2D app
Approval	WRAS approved — direct mains
Warranty	3 years

SYSTEM OVERVIEW	
Part number	ATX-300H 4.5
Availability	In stock — ships same or next working day
Pump position	Beside or in front of the vessel — specify at order
Loft installs	Confirm hatch clearance and joist loading for the filled vessel
Suited to	2–4 bed homes upwards · two or more showers at once · rain heads · unvented
Combined warranty	Tank 5 years · Pump 3 years
Supplied by	Anglian Pumping Services — established 1975

HOW IT WORKS

- 1 The WB-Compact 4.5 charges the sealed 300 L vessel up to 4.5 bar; 180 L is held ready
- 2 Open a tap and the stored volume delivers an instant boost — 27 L/min at up to 4.5 bar for up to 11 min
- 3 The pump measures incoming pressure and adds only the shortfall to the 4.5 bar set point
- 4 Stored volume used? Boosting continues at 12 L/min at 3.0 bar; the vessel recharges up to 4.5 when demand stops

Specification notes. Direct-mains system — continuous flow after discharge is limited to 12 L/min under the Water Fittings Regulations. Appliances rated below 4.5 bar need their own PRV. Loft installs: check the vessel against the hatch and spread the filled weight across joists. If 3.2 bar is enough, see the standard ATX-300H.

TWO-PHASE OPERATION

Phase 1 — stored	27 L/min @ up to 4.5 bar
Duration	Up to 11 min
Peak burst	Up to 80 L/min
Phase 2 — continuous	12 L/min @ 3.0 bar
Recharge	Automatic on demand stop

Flow rates depend on incoming mains supply

Established 1975

In stock

Fast dispatch