



WaterBoost

Nook 55 Pop

Compact break tank & booster system for flats and apartments

Part No. WB-55 Pop

Get in touch



WhatsApp
07464 644 830

waterboost.co.uk
anglianpumping.com

IN STOCK · FAST DISPATCH

Boosted water for flats. Fits in a cupboard.

The WaterBoost Nook 55 Pop is the smallest complete water boosting system in the range: a 55 litre WRAS-approved break tank with a DAB Esybox Pop variable-speed pump in front, prebuilt on a single base. Max 65 L/min at 3.2 bar from a 550 × 510 mm footprint — the legal way to boost a flat, an upper floor or a small home above the 12 L/min direct-mains limit.



55 L

Break tank

65 L/min

Max flow @ 3.2 bar

13+ min

Shower on 8 L/min main

550×510 mm

Footprint (L×D)

5 yr

Tank warranty

KEY FEATURES

- Made for flats, apartments and 1–2 shower homes
- Fits under a worktop, in a hallway or airing cupboard
- Break tank — legal above the 12 L/min mains limit
- Connects to your own supply after the stopcock
- Variable-speed inverter — constant pressure, no surging
- Keeps a combi boiler above its 1 bar firing pressure
- Quiet permanent-magnet pump, 9 kg
- Byelaw 30 kit, ball valve and insulation pre-fitted
- DAB H2D app — monitoring, Power Shower mode

WHAT'S INCLUDED

Tank	55 L Polytank rectangular, WRAS approved, insulated
Pump	DAB Esybox Pop variable-speed booster
Base	550 mm mounting base, pump in front of tank
Valve	½" BS1212 ball valve & float (pre-fitted)
Pipework	22 mm tank connector, 15 mm service valve, flexi
Kit	Byelaw 30 kit (pre-fitted to tank)

IDEAL FOR

- Top-floor and upper-floor flats
- Converted houses and maisonettes
- Small homes, annexes and garden rooms
- Combi boilers dropping out on low pressure



TANK — Polytank 55 L

Capacity	55 litres (12 gal) to waterline
Approval	WRAS approved
Material	Polyethylene, insulated
Colour	Black
Dimensions	500 × 300 × 525 mm
Byelaw 30 kit	Pre-fitted
Ball valve	½" BS1212 Pt 2, pre-fitted
Connections	22 mm outlet, 15 mm service valve
Warranty	5 years

PUMP — DAB Esybox Pop

Model	DAB Esybox Pop (60243046)
Type	Variable-speed inverter, permanent magnet
Performance	Max 65 L/min at 3.2 bar
Protection	IPX5 — indoor or outdoor
Dimensions	122 × 209 × 225 mm
Weight	9 kg
Connectivity	DAB H2D app
Supply	230 V 50 Hz single-phase
Approval	Certified for drinking water
Warranty	3 years (DAB)

SYSTEM OVERVIEW

Part number	WB-55 Pop
Availability	In stock — ships same or next working day
System footprint	550 × 510 mm on base, pump in front of tank
Sizing	1–2 shower homes, one outlet at a time, mains 8 L/min or more
Shower run time	~14 min at 12 L/min on an 8 L/min mains (see table)
Combined warranty	Tank 5 years · Pump 3 years
Supplied by	Anglian Pumping Services — established 1975

HOW IT WORKS

- 1 Mains fills the 55 L tank through the float valve at whatever rate your supply manages
- 2 The Esybox Pop draws from the tank and holds the pressure you set, up to 3.2 bar
- 3 A 12 L/min shower drains the tank by only the difference — 4 L/min on an 8 L/min main
- 4 Tank refills in about 7 minutes once the water's off; the pump rests until the next draw

Specification notes. Sized for one outlet at a time; two showers together drain the tank in under four minutes — for that, or a mains under 8 L/min, see the WB-INT Slimline 300 or Advant Slim 400. Not for Category 5 fluids (see WB-55 Pop Cat 5). Connect the overflow to a warning pipe; fit an inlet restrictor if the warning pipe cannot take the incoming flow.

SHOWER RUN TIME — 12 L/min shower

Mains 6 L/min	~9 min
Mains 7 L/min	~11 min
Mains 8 L/min	~14 min
Mains 9 L/min	~18 min
Mains 10 L/min	~27 min
Mains 12 L/min +	Continuous
Run time = 55 L ÷ (12 – mains L/min)	

Established 1975

In stock

Fast dispatch